

Data sheet

BenQ RP6502

large format touch screen



- Android 8.0 OS System
- Integrated Soundbar
- Air Quality Sensor CO₂ – PM_{2.5} – PM₁₀
- Account Management System (AMS)
- Germ-Resistant Screen
- Duo Window / OPS-Slot




| | |
|-----------------------|--|
| | Model : RP6502 |
| | Art. No. / EAN Code : 9H.F6MTK.DE1 / 471 8755 08204 7 |
| Panel | Type : 165.1 cm / 65" Wide TFT, IPS-Panel |
| | Native resolution : 3840 x 2160 4K UHD / 16:9 |
| | Panel / Pixel pitch : 10 Bit / 0.5 mm (h) x 0.37 (v) |
| | Cover Glass Thickness / Hardness : 4 mm / 7H |
| | AG coating : AG80 surface (anti-glare and germ-resistant) |
| | Backlight : Direct LED |
| | Viewing angle H / V : 178° / 178° |
| | Contrast (static) : 1200:1 |
| | Brightness : 350 cd/m ² |
| | Response time : 8 ms |
| Connection | Input front : HDMI x1 (2.0), USB type A x2 (USB 3.0 x2), USB type B x1, USB-C x1 |
| | Input back : Power AC, VGA, Line in (3.5mm), Microphone, HDMI x2 (2.0), USB type A x2 (USB 2.0 x1; USB 3.0 x1), USB type B x2, RJ45, RS232, OPS |
| | Output : Line out (3.5mm), HDMI out, SPDIF out |
| Control | Touch technology : Multitouch (Infrared) 20 points |
| | Resolution / Capacity : 32767 x 32767 / 20 simultaneous touches |
| | PC compatibility : Win7/8/10, MAC OS X10.11~10.12, Chrome OS 58, Ubuntu16.04, Fedora 8, OpenSuse 15, Android kernel version 3.10 or above |
| | Accuracy : ±1mm |
| | Controls : On / Off -Switch, 5 OSD buttons |
| | Functions : Image Setting, Source / Volume Control, Sharpness Enhancement, Proof of Image retention, HDMI-HDCP, 10 Bit color processing, Scheduling, Ambient Light Sensor, Total turn-on time, internal temperature sensor, Low Blue Light, Flicker Free, Multiple Display Administration, Account Management System, NFC Sensor, Air Quality Sensor CO ₂ – PM _{2.5} – PM ₁₀ , Duo Window |
| Extra | Software : Android 8.0 OS, EZWrite 5.0, InstaShare, WPS (office viewer App), XSign |
| | Speaker : 16W x 2 Soundbar, 15W x 1 Subwoofer |
| | Storage memory : 32 GB |
| | Mounting : 600 x 400 mm / M8 x 20 mm |
| | Mounting direction : Landscape |
| | Operation time hours / days : 18 / 7 |
| Energy | Power supply : Internal |
| | Voltage for operation : 100 ~ 240 VAC; 50 / 60 Hz |
| | Power consumption (typ.) : 142 W |
| | Sleep mode / off : < 0.5 W / 0.5 W |
| Certification | Safety : CE, Energy Star 8.0 |
| Environment | Operation : + 0 ~ +40°C ; 10 ~ 80% humidity |
| | Storage : - 10 ~ +60°C ; 10 ~ 90% humidity |
| Characteristic | Weight net: 44 kg |
| | Housing color / Material : black / metal |
| | Dimension (W x H x D) : 1506 x 951 x 121.5 mm |
| | Accessories : Quick start guide, Remote incl. batteries, Software license card, Power- / USB touch- / USB type C- / HDMI- and VGA-cable, 2x touch pen with NFC, Manual (electronic), Wallmount |
| | Warranty term : 3 years OSE (on site exchange) |





Data sheet

Input and output terminals



Dimension



Latest Update 2021-05-14
 Datasheets also available on: www.BenQ.nl, www.BenQ.be
 BenQ Benelux B.V., Meerenakkerweg 1-17, 5652 AR, Eindhoven



Because it matters