

Tempo™ Flat Panel Wall Mount System **SKU: AS3LD**



This all-in-one configurable wall mounting system is designed to improve efficiency by streamlining installation workflow. AV professionals can increase productivity and add money to the bottom line with this new system, especially for mass rollouts. Install on any wall and neatly store AV devices with simple, unparalleled service access. Install 2-6 small devices behind the display on integrated Lever Lock™ storage panels. Tempo Wall Mount System is thoughtfully designed with feedback from installers for faster deployments.

Both AS3LD and AS3LDP7 include six cable management clips for a professional-looking installation. Both SKUs also ship with a home latch lockout clip that prevents the home latch from accidentally locking until pull cords are properly stowed.

Accelerate AV Installations

- One part number, one box, one order!
- Ship to site pre-loaded with small devices and cabling.

Save Money

- Reduce onsite installation personnel and time.
- Minimize last-minute shipping costs of missing parts.

Feature Flexibility

- Wall plate and extending interface design facilitates centering display in the right position.
- 10° of adjustable display tilt in 2.5° increments.

Streamlined for Success

- Total installation depth facilitates ADA compliance*
- OSHPD approved and UL & TUV certified.
- Up to 1" (25 mm) post-install leveling adjustment.

**When display depth is less than 2" (51 mm)*

Integrated Storage

- Ships with two 15"x10" Lever Lock™ plates with space to add more.
- Storage plates can be moved along the mounting rail for best placement of components.
- Includes six cable management clips to keep cables tidy for a professional-looking installation.
- Lever Lock plates allow for 1 RU, 1.75" (44 mm), of storage clearance between the back of the display and the storage panel at 0-degree tilt.

Simplify Service

- 12.6" (320 mm) of service depth and 10.65" (271 mm) of service extension.
- Open wall plate for easy positioning of power and data sources and in-wall storage.
- Home latch lockout clip prevents home latch from accidentally locking until pull cords are properly stowed.

Specifications

Dimensions &

Measurements

Lateral Shift	Yes
Minimum Depth	4.98 cm (2 in)
Overall Dimensions	42.03" x 19.75" x 1.96" (1068 x 502 x 50 mm)
Product Weight	29.48 lbs
Shipping Dimensions	47.64" x 22" x 2.76" (121 x 55.9 x 7 cm)
Shipping Weight	16.35 kg (36.1 lbs)
Typical Screen Size	49" - 86" (1244mm - 2184mm)
Wall Stud Compatibility	• 16" O.C. • 24" O.C.
Weight Capacity	200 lbs (90.7 kg)

Characteristics &

Features

Adjustability	<ul style="list-style-type: none">• Extension• Lateral Shift• Micro-Adjustable• Tilt
---------------	---

Application	Wall
-------------	------

Color	Black
-------	-------

Includes PDU	No
--------------	----

Orientation	Landscape
-------------	-----------

Post-Installation Leveling Roll	1" (25 mm)
---------------------------------	------------

Solution Type	Universal
---------------	-----------

Special Features	ADA Compliant
------------------	---------------

TAA Compliant	No
---------------	----

Tilt	<ul style="list-style-type: none">• -10° / +0°• 2.5° increments
------	--

UPC	841872177564
-----	--------------

VESA Mounting Pattern	up to 970 x 450 mm
-----------------------	--------------------

Certifications &

Warranties

Certifications	<ul style="list-style-type: none">• cULus• OSHPD• TUV• UL
----------------	--

Source: <https://www.legrandav.com/products/mounts/display-tv-mounts/tempo-flat-panel-wall-support-system/as3ld>