



WIRE ADDRESS

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
Shell	Shell

Electrical Test:

- 1.100% TEST OPEN SHORT MIS-WIRE.
- 2.CONTACT RESISTANCE:3Ω MAX.
- 3.INSULATION RESISTANCE:5MΩ MIN.
- 4.HI-POT:300V DC/10MS.

E	4SP PVC BEIGE		G	ROLINE RS232 Cable, DB9 M - F, 3 m										
D	Screw:#4-40UNC 2.3*38.3mm(BEIGE MOLD NICKEL PLATED)	4	PCS											
C	DB 9P FEMALE(Black Insulator, Nickel Plated, PIN Gold Plated)	1	PCS									Item	11.01.6230	
B	DB 9P MALE(Black Insulator, Nickel Plated, PIN Gold Plated)	1	PCS									Draw	Sam	Date: 2014.10.21
A	NON-UL 30AWG*9C +AE OD=5.0mm,BEIGE PVC JACKET.	1	PCS									Approval		
NUMBER	PRODUCT SPECIFICATIONS		Quantity	Unit	Duty	F16	BOM.NO: 10124							
					Sample NO.	2016C42040A		Proportion:	1:1	Unit(mm)	A4			