




Datenblatt - Fiche technique - Data sheet

**11.03.1559**





ROLINE Int. SATA 3.0 Gbit/s HDD-Kabel mit Schnappverschluss, 1,0m

ROLINE Câble SATA 3.0 Gbit/s interne avec attache, 1,0 m

ROLINE Internal SATA 3.0 Gbit/s Cable with Latch, 1 m

# ROHS-COMPLIANT

LTR	REV.	DESCRIPTION	DATE
 *2	F	ECR #080409-2 EDIT PACKING,ADD BAR CODE	04/09/08'
 *2	G	ECR #080618-3 EDIT PACKING,ADD BARCODE NO.	06/18/08'



WIRING TABLE

CN1		CN2
1	DRAIN WIRE	1
2		2
3		3
4	DRAIN WIRE	4
5		5
6	DRAIN WIRE	6
7		7

140-1265-2	11.03.1559-50	1000±20	7611990168514
140-1265-1	11.03.1554-50	500±10	7611990168507
DWG	P/N	L±T(mm)	BAR CODE NO.

- TEST:
- 100% OPEN & SHORT WITH MISS WIRE TEST
  - TEST CONDITION:
  - CONDUCTANCE RESISTANCE: 5 ohm.
  - SHORT OPEN DETERMINANT: 20K ohm.
  - INSULATION RESISTANCE: 5M ohm AT DC 300V.
  - PACKING: EACH PC / POLYBAG + HEADER CARD + BAR CODE LABEL.
  - 50 PCS / CTN.

ITEM	DESCRIPTION	QTY
3	OUTER MOLD:35P PVC BLACK	A/R
2	SATA 7P G/F BLACK, W/SPRING (WITH LATCH)	2SETS
1	UL2725(26AWG*2C+2D+AE)*2C OD:2.2*7.8MM RED(PANTONE 200C)	A/R

Tolerance Inch	M/M
X	.015 .30
.XX	.010 .10
.XXX	.005 .05
Draw	DATE
PANNIE	06/18/08'
Check	Customer P/N:
App'd	Customer T-RAG
Scale	NONE
Units	m/m
Dwg No.	140-1265
REV:	G
Sheet	1/1

**Rotronic Co., Ltd.**

SATA W/LATCH CABLE STRAIGHT TO STRAIGHT