

Technical Specifications

MOBOTIX Vaxtor UIC - Railway Code Recognition App

Recognition of International Union of Railways Wagon and Coach Numbers (UIC)

The certified Vaxtor UIC - Railway Code Recognition App recognizes, based on deep learning processes UIC codes (International Union of Railways Wagon and coach numbers) which adhere to the International standard. The OCR engine takes advantage of many current integrations and publishing capabilities that have been developed over many years.

- Recognition of the UIC Codes
- Real time results for UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel
- Stop / Go and slow speed (<10 km/h) applications (depending on installation and module selection)</p>
- MOBOTIX events via MxMessageSystem
- Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB
- meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces
- Two lists for individual actions (e.g. access granted/denied, alarm, etc.)
- Free flow and signaled mode



MOBOTIX

Technical Specifications

MOBOTIX Vaxtor UIC - Railway Code Recognition App

Product Information

Product Name	Vaxtor UIC - Railway Code Recognition App
Order Code	Mx-APP-VX-UIC
Supported MOBOTIX Cameras	Mx-M73A, Mx-S74A
Minimum Camera Firmware v7.1.4.x	
MxManagementCenter compatibility	 min. MxMC v2.4.3 Configuration: Advanced Config license required Event Search: Smart Data Interface license included
MOBOTIX HUB com-	■ min. MOBOTIX HUB version: 2020 R3

min. MOBOTIX HUB license level (Analytics Events): L2

min. MOBOTIX HUB license level for Event Search Plug-In: L4

Product Features

patibility.

• •	 Recognition of cargo container codes according to ISO 6346 Real time results: Container Code
	 Owner and corresponding origin
	■ Container Type
	Container Dimensions
	Control Digit
	Control Digit Validation
	Recognition log (Smart Data / Event Search via MxManagementCenter)
1	MOBOTIX events via MxMessageSystem
	Two lists for individual actions (e.g. access granted/denied, alarm, etc.)
	Free flow and Signaled mode

Maximum number of recog- 1

nition areas	
Maximum number of enrolled UIC codes	5000 per list
Meta Data / Statistic formats	JSON, XML

Trial License	30-day trial license pre-installed
MxMessageSystem sup- ported	Yes
Integration Interfaces	 MxMC Smart Data IP Notification Milestone X-Protect (Analytics Events, Transmission Plug-In) Vaxtor Helix Genetec Security Center (Custom Events, Bookmarks) generic 3rd party integration through FTP and / or XML / JSON via HTTP(S) compare supported camera's interfaces
MOBOTIX Events	Yes
ONVIF Events	Yes (Generic Message event)

Supported Railway Codes

Supported Railway Codes	Wagon numbers / codes according to the specification of the International
	Union of Railways

Scene Requirements

Character Height	20px - 50px
Maximum Vertical Angle	30°
Maximum Horizontal Angle	< 25°
Maximum Tilt Angle	< 25°

Technical App Specifications

Synchronous / Asyn- chronous App	asynchronous
Simultaneous execution of other apps	No
Accuracy	min. 99% (considering scene requirements)

Technical Specifications

MOBOTIX Vaxtor UIC - Railway Code Recognition App

Processed frame rate	typ. 2 fps
Detection time	typ. 900 ms per wagon

