


NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel TEST:
TEST LIMIT:ISO11801 Channel Class EA
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS2.0 AND REACH compliant
5. Spray WORD:CAT6A U/FTP 4x2x32AWG/7 Ultraflex LSZH-TPE ISO11801 & EN50173 & ANSI/TIA568C.2
6. Minimum of the bending radius is 15mm(Suitable for all meters)

PIN OUT



	CN1 (568B)		CN2 (568B)
WHITE-ORANGE	1	—	1 WHITE-ORANGE
ORANGE	2	—	2 ORANGE
WHITE-GREEN	3	—	3 WHITE-GREEN
GREEN	6	—	6 GREEN
BLUE	4	—	4 BLUE
WHITE-BLUE	5	—	5 WHITE-BLUE
WHITE-BROWN	7	—	7 WHITE-BROWN
BROWN	8	—	8 BROWN
SHELL		—	SHELL
			DRAIN

MATERIAL LIST

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
③	OVER MOLD	75A PVC YELLOW(PANTONE135C)	2	
②	PLUG	RJ45 8P8C Shielded Plug, PIN GOLD PLATED 3u", THE SHELL PLATED NICKEL, COLOUR: TRANSPARENT	2	
①	CABLE	CAT. 6A U/FTP CABLE (32AWG BC*1P+AL-FOIL)*4+DRAIN JACKET:ULTRAFLEX LSZH-TPE/YELLOW(PANTONE135C), OD:3.6±0.2MM	1	
		NEW	2022-07-01	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

Item NO.	Length (mm)
21.44.3320	150±10
21.44.3321	300±10
21.44.3322	500±20
21.44.3323	1000±20
21.44.3324	1500±30
21.44.3325	2000±30
21.44.3326	3000±50
21.44.3327	5000±100

DESC. ROLINE GREEN Cat. 6A U/FTP Patch cord 10G Slim Type Ultraflex LSZH-TPE, yellow

SECOMP